

LSM SERIES**STANDARD KNOCK-DOWN SIDE MOUNT STRIP**

- Ideal for flush, stem or row mounting
- Pre-finished 23 ga steel in a baked white enamel
- UL listed for dry or damp locations



Dimensions subject to change, inquire at factory for latest data



ENERGY SAVING FLUORESCENT FIXTURES T12 MAGNETIC HO						
MODEL NO.	QTY	LAMP TYPE		DIMENSIONS		
				L	W	D
LSM124HO	1LT	F24T12HO	RAPID START	24IN	4-1/4IN	2-3/4IN
LSM136HO	1LT	F36T12HO	RAPID START	36IN	4-1/4IN	2-3/4IN
LSM148HO	1LT	F48T12HO	RAPID START	48IN	4-1/4IN	2-3/4IN
LSM172HO	1LT	F72T12HO	RAPID START	72IN	4-1/4IN	2-3/4IN
LSM196HO	1LT	F96T12HO	RAPID START	96IN	4-1/4IN	2-3/4IN
LSM224HO	2LT	F24T12HO	RAPID START	24IN	4-1/4IN	2-3/4IN
LSM236HO	2LT	F36T12HO	RAPID START	36IN	4-1/4IN	2-3/4IN
LSM248HO	2LT	F48T12HO	RAPID START	48IN	4-1/4IN	2-3/4IN
LSM272HO	2LT	F72T12HO	RAPID START	72IN	4-1/4IN	2-3/4IN
LSM296HO	2LT	F96T12HO	RAPID START	96IN	4-1/4IN	2-3/4IN

NOTE: All above UL listed damp locations

ENERGY SAVING FLUORESCENT FIXTURES T12 MAGNETIC BI-PIN						
MODEL NO.	QTY	LAMP TYPE		DIMENSIONS		
				L	W	D
LSM120I	1LT	F20T12	PRE-HEAT	24IN	3-1/8IN	1-7/8IN
LSM130HR	1LT	F30T12	RAPID START	36IN	3-1/8IN	1-7/8IN
LSM134HR	1LT	F34T12	RAPID START	48IN	3-1/8IN	1-7/8IN
LSM220I	2LT	F20T12	INSTANT START	24IN	3-1/8IN	1-7/8IN
LSM230R	2LT	F30T12	RAPID START	36IN	3-1/8IN	1-7/8IN
LSM234R	2LT	F34T12	RAPID START	48IN	3-1/8IN	1-7/8IN
LSM2230R	2LT TANDEM	F30T12	RAPID START	72IN	3-1/8IN	1-7/8IN
LSM2234R	2LT TANDEM	F34T12	RAPID START	96IN	3-1/8IN	1-7/8IN

NOTE: All above UL listed dry locations ONLY

ENERGY SAVING FLUORESCENT FIXTURES T8 ELECTRONIC						
MODEL NO.	QTY	LAMP TYPE		DIMENSIONS		
				L	W	D
E-LSM117	1LT	F17T8	INSTANT START	24IN	3-1/8IN	1-7/8IN
E-LSM125	1LT	F25T8	INSTANT START	36IN	3-1/8IN	1-7/8IN
E-LSM132	1LT	F32T8	INSTANT START	48IN	3-1/8IN	1-7/8IN
E-LSM217	2LT	F17T8	INSTANT START	24IN	3-1/8IN	1-7/8IN
E-LSM225	2LT	F25T8	INSTANT START	36IN	3-1/8IN	1-7/8IN
E-LSM232	2LT	F32T8	INSTANT START	48IN	3-1/8IN	1-7/8IN
E-LSM2225	2LT TANDEM	F25T8	INSTANT START	72IN	3-1/8IN	1-7/8IN
E-LSM2232	2LT TANDEM	F32T8	INSTANT START	96IN	3-1/8IN	1-7/8IN

NOTE: All above UL listed dry locations ONLY

AVAILABLE ADDERS/OPTIONS (Some may be special order, please inquire at factory)

- 277 volt
- Cord & plug (2 or 3 wire)
- Custom sizes available for HO/Slimline
- Dimming ballast
- Emergency back-up
- Pull chain switch
- Stems (3/8in diameter)
- Zero degree ballast

