


## FIBD SERIES

### MOISTURE & DUST RESISTANT FIBERGLASS UNIT

- Ideal for flush mounting - please specify wall or ceiling mount
- Pre-finished 23 ga steel in a baked white enamel protected by a gasketed enclosure
- Fiberglass upper body & acrylic diffuser locked together by latches
- UL listed for damp/wet locations
- Clear acrylic included



Dimensions subject to change, inquire at factory for latest data



ENERGY SAVING FLUORESCENT FIXTURES T12 MAGNETIC / T12 MAGNETIC HO						
MODEL NO.	QTY	LAMP TYPE		DIMENSIONS		
				L	W	D
FIBD220I	2LT	F20T12	PRE-HEAT	26IN	6-3/4IN	4-3/8IN
FIBD234R	2LT	F34T12	RAPID START	52IN	7-1/2IN	6IN
FIBD224HO	2LT	F24T12HO	RAPID START	26IN	6-3/4IN	4-3/8IN
FIBD248HO	2LT	F48T12HO	RAPID START	52IN	7-1/2IN	6IN
FIBD296HO	2LT	F96T12HO	RAPID START	101-3/4IN	7-1/2IN	6IN
*FIBD296HO-W	2LT	F96T12HO	RAPID START	101-3/4IN	7-1/2IN	6IN

\* Wall mount only

ENERGY SAVING FLUORESCENT FIXTURES T8 ELECTRONIC						
MODEL NO.	QTY	LAMP TYPE		DIMENSIONS		
				L	W	D
E-FIBD232	2LT	F32T8	INSTANT START	52IN	7-1/2IN	6IN

#### AVAILABLE ADDERS/OPTIONS (Some may be special order, please inquire at factory)

- 277 volt
- Clear prismatic polycarbonate (Lexan) & tamperproof latches (add suffix **-PC**)
- Emergency back-up
- Zero degree ballast

